

**Bulk material delivery 5 bar (75 psi)****Tube:** black conductive NR - abrasion resistant.**Reinforcement:** high tensile textile cords.**Cover:** black conductive SBR/NR - abrasion and ozone resistant.**Application:** bulk material delivery.

Specially designed for dry cement, grain and animal feed transfer.

Constant operation: -30 °C +80 °C (-22 °F +176 °F)

												
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
75,0	3"	93,00	3,66	5	75	15	225				2,310	1,56
90,0	3 1/2"	102,00	4,02	5	75	15	225				2,060	1,39
90,0	3 1/2"	110,00	4,33	5	75	15	225				3,140	2,12
100,0	4"	120,00	4,72	5	75	15	225				3,450	2,32
102,0	4"	114,00	4,49	5	75	15	225				2,310	1,56
102,0	4"	118,00	4,65	5	75	15	225				2,710	1,83
102,0	4"	120,00	4,72	5	75	15	225				3,130	2,11
110,0	4 5/16"	122,00	4,80	5	75	15	225				2,470	1,66
127,0	5"	145,00	5,71	5	75	15	225				3,800	2,56

**Bulk material delivery 10 bar (150 psi)****Tube:** black conductive NR - abrasion resistant.**Reinforcement:** high tensile textile cords.**Cover:** black conductive SBR/NR - abrasion and ozone resistant.**Application:** bulk material delivery in heavy duty applications.

Specially designed for dry cement, grain and animal feed transfer.

Constant operation: -30 °C +80 °C (-22 °F +176 °F)

mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
76,0	3"	92,00	3,62	10	150	30	450				2,120	1,43
102,0	4"	118,00	4,65	10	150	30	450				2,860	1,93
127,0	5"	143,00	5.63	10	150	30	450				3.530	2.38

**STREAM FLOW**

Шланги и воздуховоды

streamflow@inbox.ru

ООО «СТРИМФЛОУ»

8 (925) 741-15-81 (79) (77)